

WHEELS

Product group	Wheels
Item number	10000025
Valid wheel size	12.5 / 80 - 18
Brand	Alliance
Tread pattern	320 Value Plus
Valid rim size	11 x 18 S
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	2650
Speed complete wheel [km/h]	30
Nettogewicht [kg] (gültig)	57,01
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15212332
LI / SI / PR	145 A6 / 142 A8, 12 PR
Load capacity 1 [kg]	2900
Speed 1 [km/h].	30
Load capacity 2 [kg]	2650
Speed 2 [km/h].	40
Maximum air pressure [bar].	3,70
TL/TT	TL
Tyre colour	Black

E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	308
Stat. radius (SLR) [mm]	407
Rolling circumference [mm].	2803
Tread depth (mm)	12,0
Assembly Item no. Rim	• 31210145
Load capacity of rim 1 [kg]	4250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	30
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig

Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201039
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve length [mm]	55.0
Valve angle [°]	gerade