

## **TYRES**

| Product group   | Tyres            |  |
|-----------------|------------------|--|
| Item number     | 10000028         |  |
| Valid tyre size | VF 600 / 70 R 30 |  |
| LI / SI / PR    | 170 D / 167 E    |  |
| TL/TT           | TL               |  |
| Brand           | Trelleborg       |  |
| Tread pattern   | TM1000PT         |  |



## Notes and features

- The Trelleborg TM1000 Progressive Traction is a VF tyre for high performance tractors.
- Compared to standard tyres, it offers up to 40% higher load capacity at the same air pressure or the same load capacity at 40% less air pressure.
- Its special lugs with double edge ensure very good grip and low slippage.
- The tyre offers very high load capacities, low soil compaction and excellent traction.



## **Technical Informations**

| Item number                  | 10000028         |
|------------------------------|------------------|
| EAN                          | 8059971030891    |
| Valid tyre size              | VF 600 / 70 R 30 |
| LI / SI / PR                 | 170 D / 167 E    |
| TL/TT                        | TL               |
| Brand                        | Trelleborg       |
| Tread pattern                | TM1000PT         |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| ECE regulation number        | ECE 106          |
| Nettogewicht [kg] (gültig)   | 190,15           |
| Recommended rim size         | DW21B            |
| Permitted rim size           | DW20B            |
| Section width (mm)           | 615              |
| Outer diameter of tyre [mm]. | 1600             |
| Stat. radius (SLR) [mm]      | 695              |
| Speed Radius Index (SRI)     | 750              |
| Rolling circumference [mm].  | 4785             |
| Tread depth (mm)             | 57,0             |
| Number of lugs               | 20x2             |
| Tyre capacity 75% [ltr.]     | 428.00           |
| E-Ready                      | No               |



## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 170 D | 6000               | 65           |               | 2,40                        |              |
| 167 E | 5450               | 70           |               | 2,40                        |              |