

TYRES

Product group	Tyres
Item number	10000061
Valid tyre size	440 / 65 R 24
LI / SI / PR	131 A8 / 128 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65
Sonderpostenkategorie	Disassambled



Mitas

Notes and features

- The AC 65 is a powerful all-round wide tyre for use in the field and on the road.
- Thanks to its wide contact area, the soil is protected effectively.
- The wear-resistant rubber compound ensures a long service life.
- The tyre is characterised by a large air volume, guaranteeing a high transport performance.



Technical Informations

Item number	10000061
EAN	4040658099663
Valid tyre size	440 / 65 R 24
LI / SI / PR	131 A8 / 128 D
TL/TT	TL
Brand	Mitas
Tread pattern	AC 65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	73,90
Recommended rim size	14
Permitted rim size	12, 13
Maximum air pressure [bar].	1,60
Section width (mm)	445
Outer diameter of tyre [mm].	1196
Stat. radius (SLR) [mm]	543
Rolling circumference [mm].	3585
Tread depth (mm)	38,0
Number of lugs	19x2
Lug width (mm)	44
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
131 A8	1950	40			
128 D	1800	65			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.