

TYRES

Product group	Tyres	
Item number	10000070	
Valid tyre size	525 / 65 R 20.5	
LI / SI / PR	173 F, 20 PR	
TL/TT	TL	
Brand	BKT	
Tread pattern	Ridemax FL 699	





Notes and features

- The BKT Ridemax FL 699 is a radial tyre for agricultural trailers and tankers used mainly for road transport.
- The all-steel casing and reinforced bead provide excellent stability and a long service life.
- The tyre enables high loading capacities, good driving control and ride comfort.
- The tyre also performs superbly in field applications.



Technical Informations

Item number	10000070
EAN	8903094066971
Valid tyre size	525 / 65 R 20.5
LI / SI / PR	173 F, 20 PR
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 699
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	139,91
Recommended rim size	16.00
Permitted rim size	18.00
Maximum air pressure [bar].	8,00
Section width (mm)	518
Outer diameter of tyre [mm].	1200
Stat. radius (SLR) [mm]	544
Rolling circumference [mm].	3678
Tread depth (mm)	18,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 F	6500	80		8,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.