

## TYRES

Product group	Tyres
Item number	10000073
Valid tyre size	VF 500 / 50 R 17
LI / SI / PR	156 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M



## Notes and features

- Steel belted flotation tyre for versatile applications on a wide range of agricultural vehicles and trailers.
- Enormous load capacity and high transport performance due to 65 km/h approval (in some cases even 70 km/h).
- Modern, directional tread pattern for very good road characteristics as well as cleaning properties when used in fields.
- Low rolling resistance allows fuel savings.

## Technical Informations

Item number	10000073
EAN	8903094069453
Valid tyre size	VF 500 / 50 R 17
LI / SI / PR	156 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 693 M
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	62,70
Recommended rim size	16.00
Section width (mm)	503
Outer diameter of tyre [mm].	932
Stat. radius (SLR) [mm]	422
Rolling circumference [mm].	2880
Tread depth (mm)	16,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
156 D	4000	65	Free Rolling	5,00	