

WHEELS

Product group	Wheels
Item number	10000075
Valid wheel size	225 / 75 R 17.5
Brand	Sailun
Tread pattern	SAR1
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	1850
Speed complete wheel [km/h]	105



 **SAILUN**
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066117
LI / SI / PR	129 / 127 M, 16 PR
Load capacity 1 [kg]	1850
Speed 1 [km/h].	130
Load capacity 3 [kg]	1750
Speed 3 [km/h].	130
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA TR
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	52,84
ECE regulation number	ECE 54 ECE 117
Section width (mm)	225
Stat. radius (SLR) [mm]	366.11
Rolling circumference [mm].	2388
Tread depth (mm)	12,5
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 33060060
Load capacity of rim 1 [kg]	4050
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	105
Maximum air pressure [bar].	7,25
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC

Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade