

WHEELS

Product group	Wheels
Item number	10000075
Valid wheel size	225 / 75 R 17.5
Brand	Sailun
Tread pattern	SAR1
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	1850
Speed complete wheel [km/h]	105
Nettogewicht [kg] (gültig)	52,84
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



 **SAILUN**
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066117
LI / SI / PR	129 / 127 M, 16 PR
Load capacity 1 [kg]	1850
Speed 1 [km/h].	130
Load capacity 3 [kg]	1750
Speed 3 [km/h].	130
Maximum air pressure [bar].	7,25
Axle position truck	FA TR
TL/TT	TL

M+S	M+S
3PMSF	3PMSF
Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 54 ECE 117
Rolling resistance	D
Wet grip	B
Rolling noise [db].	73
Rolling noise level	B
Section width (mm)	225
Stat. radius (SLR) [mm]	366
Rolling circumference [mm].	2388
Tread depth (mm)	12,5
Assembly Item no. Rim	• 33060060
Load capacity of rim 1 [kg]	4050
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	3350
Speed Rims 2 [km/h]	50
Maximum speed [km/h].	105
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere

Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201040
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	9.7
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade