Bohnenkamp Moving Professionals

05.02.2025

RIMS

Product group	Rims
Item number	10000084
Valid rim size	AG 20.00 x 26.5 H2
Rim connection	10/281/335
Bolt hole design	В3
Offset (mm)	+30
Rim colour	Black
Brand	Jantsa





Load capacity of rim 1 [kg] 10200 Speed Rims 1 [km/h] 40 Load capacity of rim 2 [kg] 7500 Speed Rims 2 [km/h] 65 Load capacity of rim 3 [kg] 11850 Speed Rims 3 [km/h] 25 Maximum speed [km/h]. 65 Maximum air pressure [bar]. 6,00 Type of drive Angetriebene & gezogene Achse Nettogewicht [kg] (gültig) 93,00 H2 Hump

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Technical Informations

Bohnenkamp Moving Professionals

Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9005
Cavity Sealed	No
Disc thickness [mm]	13
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No