

WHEELS

Product group	Wheels
Item number	10000093
Valid wheel size	VF 500 / 50 R 17
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	16.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-100
Rim colour	Silver
Load capacity complete wheel [kg]	4000
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 10000073
LI / SI / PR	156 D
Load capacity 1 [kg]	4000
Speed 1 [km/h].	65
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	95,85
ECE regulation number	ECE 106
Section width (mm)	503
Stat. radius (SLR) [mm]	422
Rolling circumference [mm].	2880

Tread depth (mm)	16,0
E-Ready	No
Assembly Item no. Rim	• 31610336
Load capacity of rim 1 [kg]	4420
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	3250
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No

Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade