

WHEELS

Product group	Wheels
Item number	10000094
Valid wheel size	500 / 60 - 22.5
Brand	Alliance
Tread pattern	Flotation 331
Valid rim size	AG 16.00 x 22.5 H2
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Anthrazit
Load capacity complete wheel [kg]	3450
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	130,29
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15212582
LI / SI / PR	151 A8 / 163 A8, 16 PR
Load capacity 1 [kg]	3450
Speed 1 [km/h].	40
Load capacity 2 [kg]	4875
Speed 2 [km/h].	40
Maximum air pressure [bar].	3,20
TL/TT	TL
Tyre colour	Black

E-Ready	No
Antistatic	No
Direction	Left
ECE regulation number	ECE 106
Section width (mm)	503
Stat. radius (SLR) [mm]	519
Rolling circumference [mm].	3472
Tread depth (mm)	39,0
Assembly Item no. Rim	• 33060376
Load capacity of rim 1 [kg]	7250
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5300
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	40
Type of drive	Towed axle
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL7016
Valve seat	External Valve
Disc thickness [mm]	12.0

Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade