

TYRES

Product group	Tyres	
Item number	10000097	
Valid tyre size	405 / 70 R 18	
LI / SI / PR	152 A2 / 149 A4	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	BK Loader 53	



Notes and features

- The BK-Loader 53 is a tyre for loaders in industrial and heavy transport use, particularly recycling
- Its extremely deep tread pattern and rubber compound tailored to the application ensure slow tread wear e.g. on concrete slabs, and resistance to cuts and punctures
- Its specially designed aramid belt reliably protects the tyre against damages
- The special tread pattern design provides excellent lateral stability in harsh conditions
- Additionally, the tyre has excellent self-cleaning properties and good grip on wet and dry surfaces due to this tread pattern



Technical Informations

Item number	10000097
EAN	8903094069705
Valid tyre size	405 / 70 R 18
LI / SI / PR	152 A2 / 149 A4
TL/TT	TL
Brand	BKT
Tread pattern	BK Loader 53
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	115,70
Recommended rim size	13
Permitted rim size	14, 13SDC, 12, 12SDC
Maximum air pressure [bar].	3,75
Section width (mm)	407
Outer diameter of tyre [mm].	1045
Stat. radius (SLR) [mm]	458
Rolling circumference [mm].	3017
Tread depth (mm)	54,0
Number of lugs	12x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10	Loader dozer	3,75	
149 A4	3250	20	Transport	3,75	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.