

TYRES

Product group	Tyres
Item number	10000097
Valid tyre size	405 / 70 R 18
LI / SI / PR	152 A2 / 149 A4
TL/TT	TL
Brand	BKT
Tread pattern	BK Loader 53



Bohnenkamp
Moving Professionals



Notes and features

- The BK-Loader 53 is a tyre for loaders in industrial and heavy transport use, particularly recycling
- Its extremely deep tread pattern and rubber compound tailored to the application ensure slow tread wear e.g. on concrete slabs, and resistance to cuts and punctures
- Its specially designed aramid belt reliably protects the tyre against damages
- The special tread pattern design provides excellent lateral stability in harsh conditions
- Additionally, the tyre has excellent self-cleaning properties and good grip on wet and dry surfaces due to this tread pattern

Technical Informations

Item number	10000097
EAN	8903094069705
Valid tyre size	405 / 70 R 18
LI / SI / PR	152 A2 / 149 A4
TL/TT	TL
Brand	BKT
Tread pattern	BK Loader 53
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	115,70
Recommended rim size	13
Permitted rim size	14, 13SDC, 12, 12SDC
Maximum air pressure [bar].	3,75
Section width (mm)	407
Outer diameter of tyre [mm].	1045
Stat. radius (SLR) [mm]	458
Rolling circumference [mm].	3017
Tread depth (mm)	54,0
Number of lugs	12x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
153 A2	3650	10	Loader dozer	3,75	
149 A4	3250	20	Transport	3,75	