

WHEELS

Product group	Wheels
Item number	10000109
Valid wheel size	10.0 / 75 - 15.3
Brand	BKT
Tread pattern	AS 504
Valid rim size	9.00 X 15.3
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	55
Rim colour	Silver
Load capacity complete wheel [kg]	1320
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15711751
LI / SI / PR	118 A8 / 130 A8, 14 PR
Load capacity 1 [kg]	1320
Speed 1 [km/h].	40
Load capacity 2 [kg]	1900
Speed 2 [km/h].	40
Direction	Left
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	35,15
ECE regulation number	ECE 106
Section width (mm)	264
Stat. radius (SLR) [mm]	360
Rolling circumference [mm].	2404.00
Tread depth (mm)	23,0
E-Ready	No
Assembly Item no. Rim	• 10000086
Load capacity of rim 1 [kg]	2650
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,50
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade