

WHEELS

| | |
|-----------------------------------|------------------|
| Product group | Wheels |
| Item number | 10000110 |
| Valid wheel size | 10.0 / 75 R 15.3 |
| Brand | BKT |
| Tread pattern | AS 504 |
| Valid rim size | 9.00 X 15.3 |
| Rim connection | 6/161/205 |
| Bolt hole design | A2 |
| Offset (mm) | 55 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 1320 |
| Speed complete wheel [km/h] | 40 |
| Nettogewicht [kg] (gültig) | 35,15 |
| RDRA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|------------------------|
| Assembly Item no. Tyres | • 15711751 |
| LI / SI / PR | 118 A8 / 130 A8, 14 PR |
| Load capacity 1 [kg] | 1320 |
| Speed 1 [km/h]. | 40 |
| Load capacity 2 [kg] | 1900 |
| Speed 2 [km/h]. | 40 |
| Maximum air pressure [bar]. | 5,50 |
| TL/TT | TL |

| | |
|--------------------------------|----------------|
| Tyre colour | Black |
| E-Ready | No |
| Antistatic | No |
| Direction | Right |
| ECE regulation number | ECE 106 |
| Section width (mm) | 264 |
| Stat. radius (SLR) [mm] | 360 |
| Rolling circumference [mm]. | 2404.00 |
| Tread depth (mm) | 23,0 |
| Assembly Item no. Rim | • 10000086 |
| Load capacity of rim 1 [kg] | 2900 |
| Speed Rims 1 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Type of drive | Towed axle |
| Number of bolt holes | 6 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Bolt hole diameter [mm] | 21.5 |
| Bolt hole design EUWA | B18 ES 32 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| Rim centering | BC |
| Rim material | steel |
| RAL | RAL9006 |
| Valve seat | External Valve |
| Ventilation holes | No |
| Single / multi-part | einteilig |

| | |
|--------------------------|------------------|
| Hump | kein Hump |
| Valve protection | VSH |
| Cavity Sealed | No |
| Knurling | without knurling |
| Verschweißung beidseitig | No |
| Assembly Item no. Valve | • 47201035 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 15.7 |
| Valve design | Metal valve |
| Valve designation ETRTO | V3.21.1 |
| Valve length [mm] | 33.0 |
| Valve angle [°] | gerade |