

WHEELS

Product group	Wheels
Item number	10000111
Valid wheel size	10 - 16.5
Brand	BKT
Tread pattern	Skid Power SK
Valid rim size	8.25 x 16.5
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	50
Rim colour	Silver
Load capacity complete wheel [kg]	1400
Speed complete wheel [km/h]	20
Nettogewicht [kg] (gültig)	40,28
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15772121
LI / SI / PR	120 A8, 10 PR
Load capacity 1 [kg]	1400
Speed 1 [km/h].	40
Maximum air pressure [bar].	5,20
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
Direction	Left
ECE regulation number	ECE 106
Section width (mm)	270
Stat. radius (SLR) [mm]	355
Rolling circumference [mm].	2286
Tread depth (mm)	15,0
Assembly Item no. Rim	• 10000088
Load capacity of rim 1 [kg]	2000
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	1600
Speed Rims 2 [km/h]	20
Maximum speed [km/h].	20
Type of drive	Towed axle
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Bolt hole design EUWA	B18 ES 32
Countersinking	Sphere
Spherical countersink [mm].	R16
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	10
Ventilation holes	No

Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201035
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade