

WHEELS

Product group	Wheels
Item number	10000112
Valid wheel size	10 - 16.5
Brand	BKT
Tread pattern	Skid Power SK
Valid rim size	8.25 x 16.5
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	50
Rim colour	Silver
Load capacity complete wheel [kg]	1400
Speed complete wheel [km/h]	20



Technical Informations

Assembly Item no. Tyres	• 15772121
LI / SI / PR	120 A8, 10 PR
Load capacity 1 [kg]	1400
Speed 1 [km/h].	40
Direction	Right
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	40,28
ECE regulation number	ECE 106
Section width (mm)	270
Stat. radius (SLR) [mm]	355

Rolling circumference [mm].	2286
Tread depth (mm)	15,0
E-Ready	No
Assembly Item no. Rim	• 10000088
Load capacity of rim 1 [kg]	2000
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	1600
Speed Rims 2 [km/h]	20
Maximum speed [km/h].	20
Maximum air pressure [bar].	5,20
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161

Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.21.1
Valve length [mm]	33.0
Valve angle [°]	gerade