

TYRES

Product group	Tyres
Item number	10000188
Valid tyre size	210 / 95 R 16
LI / SI / PR	116 A8
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Agrimax RT 855 in this dimension is a radial tyre for towed vehicles.
- Its very good self-cleaning properties prevent soiling of the road surface when switching from field to road use.
- It is suitable for soil cultivation and transportation both in the field and on the road.

Technical Informations

Item number	10000188
EAN	8903094069965
Valid tyre size	210 / 95 R 16
Alternative size 1	7.50R16
LI / SI / PR	116 A8
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax RT 855
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	21,20
Recommended rim size	W7
Permitted rim size	W6, 6LB, 5.50F
Maximum air pressure [bar].	2,40
Section width (mm)	214
Outer diameter of tyre [mm].	806
Stat. radius (SLR) [mm]	350
Speed Radius Index (SRI)	390
Rolling circumference [mm].	2353
Tread depth (mm)	26,5
Number of lugs	20x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
116 A8	1250	40	Free Rolling	2,40	