

TYRES

Product group	Tyres	
Item number	10000205	
Valid tyre size	405 / 70 R 20	
LI / SI / PR	152 G	
TL/TT	TL	
Brand	BKT	
Tread pattern	Multimax MP 538	



Technical Informations

Item number	10000205
EAN	8903094069682
Valid tyre size	405 / 70 R 20
Alternative size 1	16.0/70R20
LI / SI / PR	152 G
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 538
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	76,59
Recommended rim size	W13
Maximum air pressure [bar].	6,00
Section width (mm)	407
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	484
Rolling circumference [mm].	3289
Tread depth (mm)	26,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
152 G	3550	90		6,00	
	3850	65		6,00	
	4080	40		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.