

RIMS

Product group	Rims
Item number	10000217
Valid rim size	3.50 x 10
Rim connection	4/85/115
Rim colour	Silver
Brand	Malz



Technical Informations

Load capacity of rim 1 [kg]	550
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	3,50
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Verschweißung beidseitig	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Ventilation holes	No
Number of bolt holes	4
Bolt hole diameter [mm]	13
Countersinking	Cone
Countersinking of the cone [°].	C60
hub hole diameter [mm].	85
Bolt hole circle diameter [mm]	115
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No