

RIMS

Product group	Rims
Item number	10000221
Valid rim size	6.75 x 17.5
Rim connection	8/221/275
Bolt hole design	M22
Offset (mm)	+55
Rim colour	Silver
Brand	Jantsa





Technical Informations	
Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	100
Load capacity of rim 2 [kg]	2800
Speed Rims 2 [km/h]	120
Maximum speed [km/h].	100
Nettogewicht [kg] (gültig)	25,00
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Disc thickness [mm]	12
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	НВ
Number of bolt holes	8
Bolt hole diameter [mm]	24
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No