

## WHEELS

Product group	Wheels
Item number	10000222
Valid wheel size	400 / 60 - 22.5
Brand	BKT
Tread pattern	Flotation 648
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	+50
Rim colour	Silver
Load capacity complete wheel [kg]	3150
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	104,84
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15712505
LI / SI / PR	148 A8 / 160 A8, 18 PR
Load capacity 1 [kg]	3150
Speed 1 [km/h].	40
Load capacity 2 [kg]	4500
Speed 2 [km/h].	40
Maximum air pressure [bar].	4,30
TL/TT	TL

Tyre colour	Black
E-Ready	No
Antistatic	No
Direction	Left
ECE regulation number	ECE 106
Section width (mm)	400
Stat. radius (SLR) [mm]	475
Rolling circumference [mm].	3233
Tread depth (mm)	22,0
Number of lugs	27x2
Assembly Item no. Rim	• 10000155
Load capacity of rim 1 [kg]	6750
Speed Rims 1 [km/h]	20
Load capacity of rim 2 [kg]	4500
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006

Valve seat	External Valve
Disc thickness [mm]	12
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade