

## **RIMS**

| Product group        | Rims          |
|----------------------|---------------|
| Item number          | 10000235      |
| Valid rim size       | 4.50 x 6      |
| Hub design           | Fork assembly |
| Type of bearing      | Ball bearing  |
| Shaft diameter [mm]. | 25            |
| Mounting length [mm] | 100           |
| Hub length [mm]      | 100           |
| Rim colour           | Silver        |
| Brand                | Malz          |
|                      |               |



## **Technical Informations**

| Load capacity of rim 1 [kg] | 260                           |
|-----------------------------|-------------------------------|
| Speed Rims 1 [km/h]         | 25                            |
| Maximum speed [km/h].       | 25                            |
| Type of drive               | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig)  | 2,30                          |
| Hump                        | kein Hump                     |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |
| RAL                         | RAL9006                       |
| Verschweißung beidseitig    | No                            |
| Offset hub                  | No                            |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



| Additional socket required | No             |
|----------------------------|----------------|
| Valve seat                 | External Valve |
| Valve hole diameter [mm]   | 11.3           |
| Preassembled valve         | No             |
| TPMS-kompatibles Ventil    | No             |