

## **RIMS**

Product group	Rims
Item number	10000241
Valid rim size	5.50 F x 18
Rim connection	9/150
Offset (mm)	+5
Rim colour	Silver
Brand	JKE



## **Technical Informations**

Load capacity of rim 1 [kg]	1350
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	21,54
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Disc thickness [mm]	12
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	9
Bolt hole diameter [mm]	17
Countersinking	Cone
Countersinking of the cone [°].	C90
hub hole diameter [mm].	150
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No