

WHEELS

Product group	Wheels
Item number	10000244
Valid wheel size	14.00 R 20
Brand	BKT
Tread pattern	Earthmax SR 33
Valid rim size	10.00 W - 20
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+114
Rim colour	Silver
Load capacity complete wheel [kg]	5300
Speed complete wheel [km/h]	100
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15735227
LI / SI / PR	164 / 160 J (166 G), 22 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	100
Load capacity 2 [kg]	5300
Speed 2 [km/h].	90
M+S	M+S
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	151,97
ECE regulation number	ECE 54
Section width (mm)	390
Stat. radius (SLR) [mm]	576
Rolling circumference [mm].	3840
Tread depth (mm)	23,0
E-Ready	No
Assembly Item no. Rim	• 33060160
Load capacity of rim 1 [kg]	5400
Speed Rims 1 [km/h]	110
Maximum speed [km/h].	100
Maximum air pressure [bar].	7,50
Number of bolt holes	10
Bolt hole design EUWA	M22
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	mehrteilig
Rim centering	HB
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13
Ventilation holes	No
Verschweißung beidseitig	No

Valve seat	Internal Valve
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve length [mm]	63.5
Valve angle [°]	103