

TYRES

Product group	Tyres
Item number	10000249
Valid tyre size	380 / 85 R 28
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Sonderpostenkategorie	Disassambled
type of damage	Dismounted





Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.



Technical Informations

Item number	10000249
EAN	4040658101793
Valid tyre size	380 / 85 R 28
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	78,63
Section width (mm)	380
Outer diameter of tyre [mm].	1352
Rolling circumference [mm].	4002
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40			
133 B	2060	50			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.