

WHEELS

Product group	Wheels
Item number	10000260
Valid wheel size	19.0 / 45 - 17
Brand	BKT
Tread pattern	AS 504
Valid rim size	16.00 x 17
Rim connection	8/221/275
Bolt hole design	A3
Rim colour	Silver
Load capacity complete wheel [kg]	3075
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	76,86
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15712419
LI / SI / PR	134 A8 / 147 A8, 16 PR
Load capacity 1 [kg]	2120
Speed 1 [km/h].	40
Load capacity 2 [kg]	3075
Speed 2 [km/h].	40
Maximum air pressure [bar].	3,10
TL/TT	TL
Tyre colour	Black

E-Ready	No
Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	465
Stat. radius (SLR) [mm]	389
Speed Radius Index (SRI)	410
Rolling circumference [mm].	2578
Tread depth (mm)	25,0
Number of lugs	18x2
Assembly Item no. Rim	• 33060099
Load capacity of rim 1 [kg]	4900
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	4150
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No

Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200570
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Rubber valve
Valve designation ETRTO	V2.03.3
Valve length [mm]	43.0
Valve angle [°]	gerade