

TYRES

Product group	Tyres
Item number	10000263
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A8 / 159 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Ridemax IT 696 is a municipal tyre for versatile applications.
- Its special tread pattern and the large contact area provide excellent grip for road applications, especially in wintry conditions.
- The tyre is ideal for transport and municipal maintenance work.
- Thanks to its strong casing, high load capacities and use on the heaviest machines are possible.
- The low rolling resistance ensures low fuel consumption.

Technical Informations

Item number	10000263
EAN	8903094070244
Valid tyre size	500 / 70 R 24
LI / SI / PR	164 A8 / 159 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax IT 696
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	123,50
Recommended rim size	DW16L
Permitted rim size	DW15L, DW18L
Maximum air pressure [bar].	4,00
Section width (mm)	503
Outer diameter of tyre [mm].	1310
Stat. radius (SLR) [mm]	602
Rolling circumference [mm].	3954
Tread depth (mm)	29,5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40		4,00	
159 D	4375	65			