

RIMS

| | |
|------------------|-----------------|
| Product group | Rims |
| Item number | 10000283 |
| Valid rim size | AG 13.00 x 15.5 |
| Rim connection | 6/161/205 |
| Bolt hole design | A2 |
| Offset (mm) | -15 |
| Rim colour | Silver |
| Brand | Diverse |



Allgemeine Produktabbildung. Artikel kann abweichen

Technical Informations

| | |
|-----------------------------|------------|
| Load capacity of rim 1 [kg] | 3550 |
| Speed Rims 1 [km/h] | 40 |
| Maximum speed [km/h]. | 40 |
| Type of drive | Towed axle |
| Nettogewicht [kg] (gültig) | 21 |
| Hump | kein Hump |
| Valve protection | VSH |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |

| | |
|---------------------------------------|----------------|
| Disc thickness [mm] | 10 |
| Verschweißung beidseitig | No |
| Ventilation holes | No |
| Rim centering | BC |
| Number of bolt holes | 6 |
| Bolt hole design EUWA | B18 ES 32 |
| Bolt hole diameter [mm] | 21.5 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R16 |
| hub hole diameter [mm]. | 161 |
| Bolt hole circle diameter [mm] | 205 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 15.7 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |