

WHEELS

Product group	Wheels
Item number	10000313
Valid wheel size	500 / 70 R 24
Brand	Nokian
Tread pattern	TRI 2
Valid rim size	DW 16 L x 24
Rim connection	8/221/275
Bolt hole design	A3
Offset (mm)	-10
Load capacity complete wheel [kg]	4375
Speed complete wheel [km/h]	10
Nettogewicht [kg] (gültig)	169,65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



nokian[®]
TYRES

Technical Informations

Assembly Item no. Tyres	• 17426017
LI / SI / PR	164 A8 / 159 D
Load capacity 1 [kg]	5000
Speed 1 [km/h].	40
Load capacity 2 [kg]	4375
Speed 2 [km/h].	65
Maximum air pressure [bar].	4,00
TL/TT	TL
M+S	M+S

Tyre colour	Black
E-Ready	No
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
ECE regulation number	not necessary
Section width (mm)	515
Stat. radius (SLR) [mm]	585
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3958
Tread depth (mm)	28,0
Tyre capacity 75% [ltr.]	311.25
Assembly Item no. Rim	• 32010700
Load capacity of rim 1 [kg]	7500
Speed Rims 1 [km/h]	10
Load capacity of rim 2 [kg]	5000
Speed Rims 2 [km/h]	10
Maximum speed [km/h].	10
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	8
hub hole diameter [mm].	221
Bolt hole circle diameter [mm]	275
Bolt hole diameter [mm]	27.0
Bolt hole design EUWA	B22 ES 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BC

Rim material	steel
Rim colour (manufacturer's designation)	Fendt Terra - red
Valve seat	External Valve
Disc thickness [mm]	10.0
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Valve protection	VSH
Cavity Sealed	No
Knurling	with knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201038
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	15.7
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade