

TYRES

Product group	Tyres
Item number	10000337
Valid tyre size	290 / 90 - 20
LI / SI / PR	168 A2 / 152 B, 18 PR
TL/TT	TT
SET	Tube + Flap
Brand	BKT
Tread pattern	EM 933 SUPER



Bohnenkamp
Moving Professionals



Notes and features

- The BKT EM 933 Super is a tyre for excavators in use for excavation or loading work.
- Its special sidewall with protruding rib allows close contact between the tyres during twin use and prevents stones from penetrating.
- An intermediate rubber ring between the two tyres is therefore no longer necessary.
- The special tread pattern provides excellent traction even in the most difficult conditions.
- The tyre also guarantees very good ride comfort and improved self-cleaning properties.

Technical Informations

Item number	10000337
EAN	8903094070183
Valid tyre size	290 / 90 - 20
LI / SI / PR	168 A2 / 152 B, 18 PR
TL/TT	TT
SET	Tube + Flap
Ventilposition	central
Brand	BKT
Tread pattern	EM 933 SUPER
TRA Code	E2
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	67,36
Recommended rim size	8.0
Maximum air pressure [bar].	9,00
Section width (mm)	295
Outer diameter of tyre [mm].	1055
Tread depth (mm)	22,5
Number of lugs	22x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
168 A2	5600	10		9,00	
152 B	3550	50		9,00	