

## TYRES

Product group	Tyres
Item number	10000351
Valid tyre size	800 / 65 R 32
LI / SI / PR	185 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 615



## Notes and features

- The BKT Ridemax FL 615 is a modern, versatile tyre for slurry tankers, manure spreaders and other towed vehicles.
- It is ideally suited for vehicles that are used in the field, but also drive on the road.
- In addition, it can also be used very well on powered harvesters.
- Its tread pattern offers very good grip and excellent self-cleaning properties.
- Noise is reduced thanks to its high tread percentage.

## Technical Informations

Item number	10000351
EAN	8903094070176
Valid tyre size	800 / 65 R 32
LI / SI / PR	185 D
TL/TT	TL
Brand	BKT
Tread pattern	Ridemax FL 615
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	317,24
Recommended rim size	DW27B
Permitted rim size	TW27B
Maximum air pressure [bar].	3,60
Section width (mm)	830
Outer diameter of tyre [mm].	1853
Stat. radius (SLR) [mm]	834
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5624
Tread depth (mm)	31,0
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 D	9250	65		3,60	