

TYRES

Product group	Tyres	
Item number	10000357	
Valid tyre size	600 / 70 R 28	
LI / SI / PR	164 B	
TL/TT	TL	
Brand	Firestone	
Tread pattern	Radial All Traction DT	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted	

Notes and features

- Agricultural tyre for high-performance tractors.
- Very good traction in fields.

- Excellent ride comfort on the road.
- Very low soil compaction.



Technical Informations

Item number	10000357
EAN	4040658102516
Valid tyre size	600 / 70 R 28
LI / SI / PR	164 B
TL/TT	TL
Brand	Firestone
Tread pattern	Radial All Traction DT
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	193,00
Recommended rim size	20
Permitted rim size	18
Section width (mm)	630
Outer diameter of tyre [mm].	1557
Stat. radius (SLR) [mm]	704
Rolling circumference [mm].	4672
Tread depth (mm)	57,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	442.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 B	5000	50			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.