Bohnenkamp Moving Professionals

RIMS

Product group	Rims
Item number	10000361
Valid rim size	6.00 x 17.5
Rim connection	10/176/225
Bolt hole design	M22
Offset (mm)	+123.25
Half centre distance (HMA) [mm]	135
Rim colour	Silver
Brand	Covex



Technical Informations

Load capacity of rim 1 [kg]	2750
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	23,94
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	11.75

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	НВ
Number of bolt holes	10
Bolt hole diameter [mm]	26
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve designation	PVR-51A