

RIMS

Product group	Rims
Item number	10000362
Valid rim size	6.75 x 17.5
Rim connection	10/176/225
Bolt hole design	B33
Offset (mm)	+129.25
Half centre distance (HMA) [mm]	141
Rim colour	Silver
Brand	Covex



Technical Informations

Load capacity of rim 1 [kg]	3000
Speed Rims 1 [km/h]	80
Load capacity of rim 2 [kg]	2750
Speed Rims 2 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	25,21
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006

Cavity Sealed	No
Disc thickness [mm]	11.75
Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	BHC
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	176
Bolt hole circle diameter [mm]	225
Valve seat	Internal Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve designation	PVR-51A