

RIMS

Product group	Rims
Item number	10000363
Valid rim size	6.75 x 17.5
Rim connection	6/161/205
Bolt hole design	B2
Rim colour	Silver
Brand	Covex



Technical Informations

Load capacity of rim 1 [kg]	3135
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	2180
Speed Rims 2 [km/h]	100
Load capacity of rim 3 [kg]	3000
Speed Rims 3 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	25,50
Hump	kein Hump
Single / multi-part	einteilig

Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	11.75
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BHC
Number of bolt holes	6
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation	TR 501
Valve designation ETRTO	V3.21.2
Valve length [mm]	38