

RIMS

| | |
|---------------------------------|---------------|
| Product group | Rims |
| Item number | 10000366 |
| Valid rim size | 7.50 x 22.5 H |
| Rim connection | 10/281/335 |
| Bolt hole design | M22 |
| Offset (mm) | +149 |
| Half centre distance (HMA) [mm] | 162 |
| Rim colour | Silver |
| Brand | Covex |



Technical Informations

| | |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 3550 |
| Speed Rims 1 [km/h] | 80 |
| Load capacity of rim 2 [kg] | 3250 |
| Speed Rims 2 [km/h] | 130 |
| Maximum speed [km/h]. | 130 |
| Type of drive | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig) | 40,25 |
| Hump | H |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |

| | |
|--------------------------------|----------------|
| Cavity Sealed | No |
| Disc thickness [mm] | 13 |
| Verschweißung beidseitig | No |
| Ventilation holes | Yes |
| Rim centering | HB |
| Number of bolt holes | 10 |
| Bolt hole diameter [mm] | 26 |
| hub hole diameter [mm]. | 281 |
| Bolt hole circle diameter [mm] | 335 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 9.7 |
| Preassembled valve | Yes |
| TPMS-kompatibles Ventil | No |
| Valve design | Metal valve |
| Valve designation | 58 MS |
| Valve designation ETRTO | V3.22.1 |
| Valve length [mm] | 58 |
| Valve angle [°] | 45 |
| Valve cap Material | Steel |