

RIMS

Product group	Rims
Item number	10000367
Valid rim size	8.25 x 22.5 H
Rim connection	10/281/335
Bolt hole design	B33
Offset (mm)	+156
Half centre distance (HMA) [mm]	169
Rim colour	Silver
Brand	Covex



Technical Informations

Load capacity of rim 1 [kg]	3600
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	130
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	41,62
Hump	H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13

Verschweißung beidseitig	No
Ventilation holes	Yes
Rim centering	BC
Number of bolt holes	10
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	Yes
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41
Valve angle [°]	gerade
Valve cap Material	Steel