

RIMS

Product group	Rims
Item number	10000385
Valid rim size	13.00 x 17
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	-15
Rim colour	Silver
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	4950
Speed Rims 1 [km/h]	25
Axle position agriculture 1	Free Rolling
Load capacity of rim 2 [kg]	4150
Speed Rims 2 [km/h]	40
Axle position agriculture 2	Free Rolling
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	25,00
Hump	kein Hump
Valve protection	VS H

Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10
Verschweißung beidseitig	No
Ventilation holes	No
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No