

WHEELS

Product group	Wheels
Item number	10000387
Valid wheel size	13 x 5.00 - 6
Brand	Deli
Tread pattern	S-247
Valid rim size	3.50 x 6 H2
Rim connection	4/60/90
Rim colour	Silver
Load capacity complete wheel [kg]	145
Speed complete wheel [km/h]	16
Nettogewicht [kg] (gültig)	3,61
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Deli Tire
ROAD SYMBIOSIS

Technical Informations

Assembly Item no. Tyres	• 19110080
LI / SI / PR	29A6 / 41 A6, 4 PR
Load capacity 1 [kg]	103
Speed 1 [km/h].	30
Load capacity 2 [kg]	145
Speed 2 [km/h].	30
Maximum air pressure [bar].	2,10
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	125
Stat. radius (SLR) [mm]	153
Rolling circumference [mm].	961
Tread depth (mm)	9,4
Assembly Item no. Rim	• 39600300
Load capacity of rim 1 [kg]	325
Speed Rims 1 [km/h]	16
Load capacity of rim 2 [kg]	145
Speed Rims 2 [km/h]	30
Maximum speed [km/h].	16
Type of drive	Towed axle
Number of bolt holes	4
hub hole diameter [mm].	60
Bolt hole circle diameter [mm]	90
Bolt hole diameter [mm]	8.5
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	1.75
Ventilation holes	No
Single / multi-part	einteilig
Hump	H2
Cavity Sealed	No
Verschweißung beidseitig	No

Assembly Item no. Valve	• 47200650
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade