

WHEELS

| | |
|-----------------------------------|----------------|
| Product group | Wheels |
| Item number | 10000387 |
| Valid wheel size | 13 x 15.00 - 6 |
| Brand | Deli |
| Tread pattern | S-247 |
| Valid rim size | 3.50 x 6 H2 |
| Rim connection | 4/60/90 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 145 |
| Speed complete wheel [km/h] | 16 |



Technical Informations

| | |
|----------------------------|--------------------|
| Assembly Item no. Tyres | • 19110080 |
| LI / SI / PR | 29A6 / 41 A6, 4 PR |
| Load capacity 1 [kg] | 103 |
| Speed 1 [km/h]. | 30 |
| Load capacity 2 [kg] | 145 |
| Speed 2 [km/h]. | 30 |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 3,61 |
| ECE regulation number | ECE 106 |
| Section width (mm) | 125 |

| | |
|--------------------------------|----------------|
| Stat. radius (SLR) [mm] | 153 |
| Rolling circumference [mm]. | 961 |
| Tread depth (mm) | 9,4 |
| E-Ready | No |
| Assembly Item no. Rim | • 39600300 |
| Load capacity of rim 1 [kg] | 325 |
| Speed Rims 1 [km/h] | 16 |
| Load capacity of rim 2 [kg] | 145 |
| Speed Rims 2 [km/h] | 30 |
| Maximum speed [km/h]. | 16 |
| Maximum air pressure [bar]. | 2,10 |
| Type of drive | Towed axle |
| Hump | H2 |
| Single / multi-part | einteilig |
| Rim material | steel |
| RAL | RAL9006 |
| Cavity Sealed | No |
| Disc thickness [mm] | 1.75 |
| Ventilation holes | No |
| Verschweißung beidseitig | No |
| Rim centering | BC |
| Number of bolt holes | 4 |
| Bolt hole diameter [mm] | 8.5 |
| hub hole diameter [mm]. | 60 |
| Bolt hole circle diameter [mm] | 90 |
| Valve seat | External Valve |
| Valve hole diameter [mm] | 11.3 |

| | |
|-------------------------|--------------|
| Preassembled valve | No |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.1 |
| Valve length [mm] | 43.0 |
| Valve angle [°] | gerade |