

## TYRES

|                 |            |
|-----------------|------------|
| Product group   | Tyres      |
| Item number     | 10000418   |
| Valid tyre size | 18.00 - 25 |
| LI / SI / PR    | 40 PR      |
| TL/TT           | TL         |
| Brand           | BKT        |
| Tread pattern   | SM 54 M    |



Bohnenkamp  
■ ■ ● Moving Professionals



## Notes and features

- The smooth and extra deep L-4S tread is ideally suited to handling empty and loaded containers, especially on hard surfaces.
- The tread consists of a highly wear and cut resistant rubber compound.
- Compared to the predecessor SM 54, the SM 54 M tread is somewhat flatter for an even longer service life.
- The extra deep and smooth tread pattern provides for a wheel with highest driving comfort and outstanding stability during lift mode.

## Technical Informations

|                              |               |
|------------------------------|---------------|
| Item number                  | 10000418      |
| EAN                          | 8903094055791 |
| Valid tyre size              | 18.00 - 25    |
| LI / SI / PR                 | 40 PR         |
| TL/TT                        | TL            |
| Brand                        | BKT           |
| Tread pattern                | SM 54 M       |
| TRA Code                     | IND4S         |
| Antistatic                   | No            |
| Tyre colour                  | Black         |
| ECE regulation number        | not necessary |
| Nettogewicht [kg] (gültig)   | 463,89        |
| Recommended rim size         | 13.00/2.5     |
| Permitted rim size           | 15.00/2.5     |
| Maximum air pressure [bar].  | 10,00         |
| Section width (mm)           | 528           |
| Outer diameter of tyre [mm]. | 1650          |
| Stat. radius (SLR) [mm]      | 750           |
| Rolling circumference [mm].  | 4880          |
| Tread depth (mm)             | 59,0          |
| E-Ready                      | No            |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
|       | 22950              | 10           |               | 10,00                    |              |