

TYRES

Product group	Tyres
Item number	10000418
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	SM 54 M



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The smooth and extra deep L-4S tread is ideally suited to handling empty and loaded containers, especially on hard surfaces.
- The tread consists of a highly wear and cut resistant rubber compound.
- Compared to the predecessor SM 54, the SM 54 M tread is somewhat flatter for an even longer service life.
- The extra deep and smooth tread pattern provides for a wheel with highest driving comfort and outstanding stability during lift mode.

Technical Informations

Item number	10000418
EAN	8903094055791
Valid tyre size	18.00 - 25
LI / SI / PR	40 PR
TL/TT	TL
Brand	BKT
Tread pattern	SM 54 M
TRA Code	IND4S
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	463,89
Recommended rim size	13.00/2.5
Permitted rim size	15.00/2.5
Maximum air pressure [bar].	10,00
Section width (mm)	528
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	750
Rolling circumference [mm].	4880
Tread depth (mm)	59,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	22950	10		10,00	