

WHEELS

Product group	Wheels
Item number	10000419
Valid wheel size	385 / 65 R 22.5
Brand	Windpower
Tread pattern	WTR 69+
Valid rim size	11.75 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Rim colour	Silver
Load capacity complete wheel [kg]	4250
Speed complete wheel [km/h]	120
Nettogewicht [kg] (gültig)	114,83
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



WINDPOWER·TYRE
Get Your Job Done

Technical Informations

Assembly Item no. Tyres	• 10466744
LI / SI / PR	164 K (158 L), 20 PR
Load capacity 1 [kg]	5000
Speed 1 [km/h].	110
Load capacity 2 [kg]	4250
Speed 2 [km/h].	120
Maximum air pressure [bar].	9,00
Axle position truck	TR
TL/TT	TL

M+S	M+S
3PMSF	3PMSF
Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 54 ECE 117
Rolling resistance	B
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
Section width (mm)	384
Stat. radius (SLR) [mm]	499
Rolling circumference [mm].	3260
Tread depth (mm)	16,8
Assembly Item no. Rim	• 31460100
Load capacity of rim 1 [kg]	5000
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	120
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26
Bolt hole design EUWA	M22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BHC

Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Ventilation holes	No
Single / multi-part	einteilig
Hump	kein Hump
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201040
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	9.7
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade