

## TYRES

Product group	Tyres
Item number	10000462
Valid tyre size	280 / 70 R 16
LI / SI / PR	112 D / 109 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



**BRIDGESTONE**

## Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

**Technical Informations**

Item number	10000462
EAN	3286341701913
Valid tyre size	280 / 70 R 16
LI / SI / PR	112 D / 109 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	31,15
Recommended rim size	W9
Permitted rim size	W8, W10
Maximum air pressure [bar].	2,40
Section width (mm)	276
Outer diameter of tyre [mm].	813
Stat. radius (SLR) [mm]	366
Speed Radius Index (SRI)	380
Rolling circumference [mm].	2442
Tread depth (mm)	36,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	46
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 D	1120	65		2,40	
109 E	1030	70		2,40	