

TYRES

Product group	Tyres
Item number	10000476
Valid tyre size	320 / 85 R 24
LI / SI / PR	127 D / 124 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

Item number	10000476
EAN	3286341698312
Valid tyre size	320 / 85 R 24
LI / SI / PR	127 D / 124 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	61,85
Recommended rim size	DW11
Permitted rim size	DW10, W10, W11
Maximum air pressure [bar].	2,40
Section width (mm)	326
Outer diameter of tyre [mm].	1148
Stat. radius (SLR) [mm]	531
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3438
Tread depth (mm)	42,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	108
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
127 D	1750	65		2,40	
124 E	1600	70		2,40	