

TYRES

Product group	Tyres
Item number	10000477
Valid tyre size	340 / 85 R 24
LI / SI / PR	130 D / 127 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor





Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.



Technical Informations

Item number	10000477
EAN	3286341689211
Valid tyre size	340 / 85 R 24
LI / SI / PR	130 D / 127 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	67,58
Recommended rim size	DW12
Permitted rim size	DW11, W11, W12
Maximum air pressure [bar].	2,40
Section width (mm)	351
Outer diameter of tyre [mm].	1187
Stat. radius (SLR) [mm]	549
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3555
Tread depth (mm)	44,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	127
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
130 D	1900	65		2,40	
127 E	1750	70		2,40	