

## TYRES

Product group	Tyres
Item number	10000480
Valid tyre size	380 / 85 R 24
LI / SI / PR	137 D / 134 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



**BRIDGESTONE**

## Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

**Technical Informations**

<b>Item number</b>	10000480
<b>EAN</b>	3286341343410
<b>Valid tyre size</b>	380 / 85 R 24
<b>LI / SI / PR</b>	137 D / 134 E
<b>TL/TT</b>	TL
<b>Brand</b>	Bridgestone
<b>Tread pattern</b>	VX-Tractor
<b>Antistatic</b>	No
<b>Tyre colour</b>	Black
<b>ECE regulation number</b>	ECE 106
<b>Nettogewicht [kg] (gültig)</b>	84,65
<b>Recommended rim size</b>	DW13
<b>Permitted rim size</b>	DW11, W11, DW12, W12, W13
<b>Maximum air pressure [bar].</b>	2,40
<b>Section width (mm)</b>	399
<b>Outer diameter of tyre [mm].</b>	1261
<b>Stat. radius (SLR) [mm]</b>	583
<b>Speed Radius Index (SRI)</b>	600
<b>Rolling circumference [mm].</b>	3776
<b>Tread depth (mm)</b>	48,0
<b>Number of lugs</b>	18x2
<b>Tyre capacity 75% [ltr.]</b>	173
<b>E-Ready</b>	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 D	2300	65		2,40	
134 E	2120	70		2,40	