

## TYRES

Product group	Tyres
Item number	10000480
Valid tyre size	380 / 85 R 24
LI / SI / PR	137 D / 134 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



**BRIDGESTONE**

## Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

## Technical Informations

Item number	10000480
EAN	3286341343410
Valid tyre size	380 / 85 R 24
LI / SI / PR	137 D / 134 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,65
Recommended rim size	DW13
Permitted rim size	DW11, W11, DW12, W12, W13
Maximum air pressure [bar].	2,40
Section width (mm)	399
Outer diameter of tyre [mm].	1261
Stat. radius (SLR) [mm]	583
Speed Radius Index (SRI)	600
Rolling circumference [mm].	3776
Tread depth (mm)	48,0
Number of lugs	18x2
Tyre capacity 75% [ltr.]	173
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 D	2300	65		2,40	
134 E	2120	70		2,40	