

## TYRES

Product group	Tyres
Item number	10000493
Valid tyre size	380 / 70 R 28
LI / SI / PR	133 D / 130 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



**BRIDGESTONE**

## Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

## Technical Informations

Item number	10000493
EAN	3286341340211
Valid tyre size	380 / 70 R 28
LI / SI / PR	133 D / 130 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	81,32
Recommended rim size	DW12
Permitted rim size	DW11, W11, W12, DW13, W13
Maximum air pressure [bar].	2,40
Section width (mm)	383
Tread width (mm)	383
Outer diameter of tyre [mm].	1294
Stat. radius (SLR) [mm]	592
Speed Radius Index (SRI)	625
Rolling circumference [mm].	3884
Tread depth (mm)	46,0
Number of lugs	19x2
Tyre capacity 75% [litr.]	158
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 D	2060	65		2,40	
130 E	1900	70		2,40	