

## TYRES

Product group	Tyres
Item number	10000495
Valid tyre size	420 / 70 R 28
LI / SI / PR	139 D / 136 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor



**BRIDGESTONE**

## Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

## Technical Informations

Item number	10000495
EAN	3286341340815
Valid tyre size	420 / 70 R 28
LI / SI / PR	139 D / 136 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	99,31
Recommended rim size	DW13
Permitted rim size	DW12, W12, W13, DW14L, W14L
Maximum air pressure [bar].	2,40
Section width (mm)	430
Outer diameter of tyre [mm].	1356
Stat. radius (SLR) [mm]	621
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4068
Tread depth (mm)	47,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	201
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
139 D	2430	65		2,40	
136 E	2240	70		2,40	